

**komet** | *Pivot*

## Komet Precision Twister (KPT) Peak

**For installation on Top of Pipe**

High-performing pivot sprinkler for top of pipe installations: with its uniform distribution pattern & optimal droplet size that minimizes wind drift, this pivot sprinkler is perfectly suitable for installations on top of pipe to irrigate tall crops



### The Product

Optimal irrigation is achieved by distributing water evenly across the entire wetted area. Tall crops, such as corn or sugarcane, may require installations where the sprinkler is mounted on top of the pivot pipe. In this setup an ideal droplet size is especially important: droplets that are too small are prone to wind drift and evaporation; droplets that are too large can cause soil sealing and compaction.

The Komet Precision Twister (KPT) Peak is the result of a ten-year development process, involving extensive research into the core elements of high-efficiency irrigation. This pivot sprinkler is designed to meet all of the requirements identified in the field - including the ability to deliver high performance for top of pipe installations.

Thanks to its optimal droplet size, the KPT Peak is the supreme solution for installations on top of pipe, where the susceptibility to wind drift is amplified. The interplay between sophisticated design, precision manufacturing and the use of high-quality materials ensures an extensive product lifespan.

### Features and Benefits:

- ▶ Excellent distribution pattern and optimized droplet size
- ▶ High energy efficiency
- ▶ Long lasting and durable design
- ▶ Suitable for nozzle sizes from 10 - 52 1/128"
- ▶ Pressure range 6 to 20 psi
- ▶ For installation on top of the pivot pipe



**KPT Peak**  
White Deflector  
Low Profile Trajectory

**KPT Link**  
Required for installation

**Komet Precision Twister**

KPT Peak



KPT Link



**komet | Precision Twister (KPT) Peak LOW PROFILE TRAJECTORY**

Deflector Specifications		Operating Parameters						Installation				
Trajectory	Grooves	Nozzle range (1/128")	Pressure range (psi)	Flow range (gpm)	Spacing max. (ft)	Top of pipe						
Low Profile Trajectory	10	10 - 52	6-20	0.44 - 21.33	20	KPT-Link connector required						
Nozzle Size (1/128")	Throw Diameter D (ft)								Stream Height S (in)			
	Installation Height H=7ft				Installation Height H=13ft							
	Pressure (psi)				Pressure (psi)				Pressure (psi)			
	6	10	15	20	6	10	15	20	6	10	15	20
10	32	38	44	49	39	46	52	56	LOW PROFILE			
16	34	40	46	51	41	47	53	58				
23	35	41	47	52	42	48	55	59				
29	36	42	48	53	43	49	56	60				
34	37	43	49	54	44	50	56	61				
40	38	44	50	55	45	51	57	62				
45	38	44	50	55	45	52	58	62				
52	39	45	51	56	46	52	58	63				

For optimal performance of the Komet Precision Twister (KPT) Peak when installed on top of pipes, it is recommended to use the maximum spacing up to the 2nd span only. Performance data regarding flow and throw in relation to installation height and deflector type shown in the table, originate from the mathematical model used in the Komet Pivot Calculator software. Performance data was obtained under ideal testing conditions and is the base for the mathematical model. Pressure refers to pressure at nozzle. Stream height is the height from the deflector to the highest droplets in the trajectory profile. Performance may be adversely affected by wind and other factors.