



INNOVATIVE
IRRIGATION

komet | *Twin*

Twin Max

For Pivots, Travelers and Solid Sets

High-performing big volume gun with long throw ranges and uniform distribution across the entire throw radius.

Innovative design for maximum efficiency and long-term durability



The Product

High-volume irrigation is beneficial for crops with greater watering requirements, and in environments that benefit from an extended throw radius. Big volume guns are an ideal solution to increase the wetted diameter at the end of a mechanized irrigation system, on travellers or for solid set applications.

Komet's TwinMax line is based on years of field experience, and has been thoroughly tested in a variety of climates and conditions around the world. A sophisticated interplay of self-adjusting mechanisms enables uniform water distribution, unprecedented throw ranges and high energy efficiency - regardless of pressure levels or external conditions.

The use of high-end materials, and a construction designed to minimize stress on the main components, ensure an especially long product lifespan.

The TwinMax models are suitable for pivot end-guns, travelers or solid set installations.

Features and Benefits:

- ▶ Long throw & uniform water distribution
- ▶ Unmatched performance at low pressure, starting at 25 psi
- ▶ High-quality materials incl. technical polymers, marine grade aluminum, chemically treated stainless steel
- ▶ Engineered to minimize wear on key components for an especially long product lifespan
- ▶ Extended nozzle range from 0.39 to 0.94 and nozzles available in small increments
- ▶ Various fixed trajectory angles available
- ▶ Pressure range from 25 to 110 psi

Available Models

Twin MAX

24°



Twin MAX

PIVOT 18°



Twin MAX

PIVOT 12°



Performance Data U.S. Units

komet | *Twin Max*

High Performance Nozzles Trajectory angle **24°**

PSI	Nozzle 0.39"		Nozzle 0.43"		Nozzle 0.47"		Nozzle 0.51"		Nozzle 0.55"		Nozzle 0.59"		Nozzle 0.63"		Nozzle 0.67"		Nozzle 0.71"		Nozzle 0.79"		Nozzle 0.87"		Nozzle 0.94"	
	GPM	DIA.	GPM	DIA.	GPM	DIA.	GPM	DIA.	GPM	DIA.	GPM	DIA.	GPM	DIA.	GPM	DIA.	GPM	DIA.	GPM	DIA.	GPM	DIA.	GPM	DIA.
25	22	135'	27	140'	32	147'	38	154'	44	163'	50	171'	57	178'	64	180'	72	181'	89	184'	107	187'	128	190'
30	24	145'	29	152'	35	159'	41	167'	48	174'	55	182'	62	190'	70	191'	79	193'	97	196'	118	199'	140	201'
35	26	155'	32	163'	38	171'	44	179'	51	186'	59	193'	67	200'	76	205'	85	209'	105	217'	127	220'	151	224'
40	28	165'	34	174'	40	183'	47	190'	55	197'	63	204'	72	211'	81	218'	91	224'	112	237'	136	242'	162	246'
45	30	175'	36	184'	43	194'	50	201'	58	207'	67	214'	76	221'	86	229'	97	236'	119	251'	144	257'	172	263'
50	31	184'	38	194'	45	204'	53	211'	62	218'	71	225'	80	232'	91	240'	102	248'	126	264'	152	272'	181	280'
55	33	191'	40	201'	47	210'	56	217'	65	225'	74	232'	84	239'	95	247'	107	255'	132	272'	159	282'	190	292'
60	34	198'	42	207'	50	217'	58	224'	67	232'	77	239'	88	246'	99	255'	111	263'	138	281'	166	292'	198	303'
65	36	202'	43	212'	52	221'	61	229'	70	236'	81	244'	92	252'	103	260'	116	269'	143	286'	173	298'	206	311'
70	37	207'	45	216'	54	225'	63	233'	73	241'	84	249'	95	257'	107	266'	120	275'	149	292'	180	305'	214	318'
80	40	216'	48	225'	57	233'	67	242'	78	251'	89	260'	102	269'	115	277'	129	286'	159	304'	192	318'	229	333'
90	42	225'	51	233'	61	241'	71	251'	83	261'	95	270'	108	280'	122	288'	137	297'	169	315'	204	330'	243	346'
100	44	231'	54	240'	64	248'	75	258'	87	268'	100	278'	114	288'	128	296'	144	305'	178	323'	215	340'	256	357'
110	47	235'	56	245'	67	255'	79	265'	91	274'	105	284'	119	293'	135	303'	151	312'	186	330'	225	348'	268	366'

P.S. The performance data were obtained under ideal testing conditions and may be adversely affected by wind and other factors. Pressure refers to pressure at nozzle. A lowered trajectory angle improves the irrigation efficiency in windy conditions. For every 3° drop of the trajectory angle the throw is reduced by approx. 3 to 4%.

To determine the throw data of above model used with an 18° trajectory angle and installed at the end of a pivot, apply a factor 0.82 to the throw data shown in the performance table.